



CLAWS - DIRECT DRIVE INSTALLATION MANUAL



claws



Company Profile



**In-house
R&D
development
team**

**Manufactures to
international
quality standard
ISO 9001:2008**



**After-sales
multi-language
Technical Support**

**Monday to Friday
from 07h00 to 18h00
GMT+2
Saturdays
08h00 to 16h30 GMT +2**

**100%
testing of
products**



**Sales and technical support
to Africa, Europe, Asia,
the Americas, Australia
and the Pacific**

Centurion Systems (Pty) Ltd reserves the right to make changes to the products described in this manual without notice and without obligation to notify any persons of any such revisions or changes. Additionally, **Centurion Systems (Pty) Ltd** makes no representations or warranties with respect to this manual. No part of this document may be copied, stored in a retrieval system or transmitted in any form or by any means electronic, mechanical, optical or photographic, without the express prior written consent of **Centurion Systems (Pty) Ltd**.



Contents

**SAFETY
FIRST**

IMPORTANT SAFETY INSTRUCTIONS

page 6

1. General Description	page 8
2. Product Specifications	page 8
2.1. Technical Specifications	page 8
2.2. Product Dimensions	page 9
2.2.1. Surface Mount	Page 9
2.2.2. Flush Mount	Page 9
Surface Mount Installations	page 10
3. Product Identification	page 11
4. Tools Required	page 12
5. Introduction	page 12
5.1. Installation Configurations	page 12
5.1.1. Orientation of Installation	page 12
5.1.2. Spike Impact Direction	page 14
6. RHS Surface Mount - Similar Direction of Travel	page 16
6.1. Configuring the Drive Linkage Assembly	page 16
6.2. Spike Module Assembly	page 19
6.3. Re-assembling the Ramp Plates and Linkage Cover	page 26
6.4. Integrating the SECTOR II with the CLAWS	page 28
6.5. Completing the Assembly	page 32
7. RHS Surface Mount - Opposing Direction of Travel	page 33
7.1. Configuring the Drive Linkage Assembly	page 33
7.2. Spike Module Assembly	page 36
7.3. Re-assembling the Ramp Plates and Linkage Cover	page 43
7.4. Integrating the SECTOR II with the CLAWS	page 45
7.5. Completing the Assembly	page 49

8. LHS Surface Mount - Similar Direction of Travel	page 51
8.1. Configuring the Drive Linkage Assembly	page 51
8.2. Spike Module Assembly	page 54
8.3. Re-assembling the Ramp Plates and Linkage Cover	page 61
8.4. Integrating the SECTOR II with the CLAWS	page 63
8.5. Completing the Assembly	page 67
9. LHS Surface mount - Opposing Direction of Travel	page 69
9.1. Configuring the Drive Linkage Assembly	page 69
9.2. Spike Module Assembly	page 72
9.3. Re-assembling the Ramp Plates and Linkage Cover	page 79
9.4. Integrating the SECTOR II with the CLAWS	page 81
9.5. Completing the Assembly	page 85
Flush Mount Installations	page 87
10. Product Identification	page 88
11. Tools Required	page 89
12. Introduction	page 90
12.1. Installation Configurations	page 90
12.1.1. Orientation of Installation	page 90
12.1.2. Spike Impact Direction	page 91
13. RHS Flush Mount - Similar Direction of Travel	page 93
13.1. Configuring the Drive Linkage Assembly	page 93
13.2. Spike Module Assembly	page 96
13.3. Preparing the Trench and Drainage System	page 103
13.4. Re-assembling the Ramp Plates and Linkage Cover	page 105
13.5. Integrating the SECTOR II with the CLAWS	page 106
13.6. Completing the Assembly	page 110

14. RHS Flush Mount - Opposing Direction of Travel	page 111
14.1. Configuring the Drive Linkage Assembly	page 111
14.2. Spike Module Assembly	page 114
14.3. Preparing the Trench and Drainage System	page 121
14.4. Re-assembling the Ramp Plates and Linkage Cover	page 123
14.5. Integrating the SECTOR II with the CLAWS	page 124
14.6. Completing the Assembly	page 128
15. LHS Flush Mount - Similar Direction of Travel	page 129
15.1. Configuring the Drive Linkage Assembly	page 129
15.2. Spike Module Assembly	page 132
15.3. Preparing the Trench and Drainage System	page 139
15.4. Re-assembling the Ramp Plates and Linkage Cover	page 141
15.5. Integrating the SECTOR II with the CLAWS	page 142
15.6. Completing the Assembly	page 146
16. LHS Flush Mount - Similar Direction of Travel	page 147
16.1. Configuring the Drive Linkage Assembly	page 147
16.2. Spike Module Assembly	page 150
16.3. Preparing the Trench and Drainage System	page 157
16.4. Re-assembling the Ramp Plates and Linkage Cover	page 159
16.5. Integrating the SECTOR II with the CLAWS	page 160
16.6. Completing the Assembly	page 164
17. Wiring Diagram	page 165
18. Installation Handover	page 166

Icons used in this manual



This icon indicates tips and other information that could be useful during the installation.



This icon denotes variations and other aspects that should be considered during installation.



This icon indicates warning, caution or attention! Please take special note of critical aspects that MUST be adhered to in order to prevent injury.



This icon indicates areas where mechanical crushing may occur

IMPORTANT SAFETY INSTRUCTIONS

ATTENTION

To ensure the safety of people and possessions, it is important that you read all the following instructions.

Incorrect installation or incorrect use of the product may cause serious harm to people and / or property.

The installer, being either professional or DIY, is the last person on the site who can ensure that the operator is safely installed, and that the whole system can be operated safely.



Warnings for the installer

CAREFULLY READ AND FOLLOW ALL INSTRUCTIONS before beginning to install the product.

- All installation, repair, and service work to this product must be done by a suitably qualified person
- Do not activate the **CLAWS** unless you can see them and can determine that the **CLAWS** are clear of people, pets, vehicles or any obstructions.
- Nothing must be placed on or near the trench covers at any time.
- No one must be near the trench covers at any time. Always keep people and objects away from the spikes' area of travel
- Children should be supervised to ensure that they do not play with or around the spikes and trench cover
- This device is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety
- Secure all easily-accessed **CLAW** controls in order to prevent unauthorised use
- Do not in any way modify the components of the automated system
- Do not install the equipment in an explosive atmosphere. The presence of flammable gas or fumes is a serious danger to safety
- Before attempting any work on the system, cut electrical power and disconnect the batteries
- The mains power supply of the automated system must be fitted with a double pole switch with contact opening distance of 3mm or greater. Use of a 5A thermal breaker is recommended
- Make sure that an earth leakage circuit breaker with a threshold of 30mA is fitted upstream of the system
- Never short-circuit the battery and do not try to recharge the batteries with power supply units other than that supplied with the product, or manufactured by Centurion Systems (Pty) Ltd

- Make sure that the earthing system is correctly constructed, and that all metal parts of the system are suitably earthed
- Safety devices must be fitted to the installation to guard against mechanical movement risks such as crushing, dragging and shearing
- It is recommended that at least one warning indicator light be fitted to every system
- Always fit a warning sign visibly to the inside and outside of the entrance and exit
- The installer must explain and demonstrate the manual operation of the system in case of an emergency, and must hand the User Guide and Safety Instructions over to the end user
- Explain these safety instructions to all persons authorised to use the system, and be sure that they understand the hazards associated with the system
- Do not leave packing materials (plastic, polystyrene, etc.) within reach of children as such materials are potential sources of danger
- Dispose of all waste products like packaging materials, worn-out batteries, etc. according to local regulations
- Always check the obstruction detection system, and safety devices for correct operation
- Neither Centurion Systems (Pty) Ltd, nor its subsidiaries, accepts any liability caused by improper use of the product, or for use other than that for which the automated system was intended
- This product was designed and built strictly for the use indicated in this documentation. Any other use, not expressly indicated here, could compromise the service life/operation of the product and/or be a source of danger
- Everything not expressly specified in these instructions is not permitted



1. General Description

CLAWS barrier spikes are designed to enhance the security at the entrance to high-volume sites. They provide a formidable deterrent to would-be criminals and due to their robust construction they are very difficult to defeat.

Clever modular design allows the **CLAWS** to be ordered ex-stock and can be configured into a variety of different lengths. The orientation of the spikes can also be easily changed depending on the direction of the traffic flow. Their external limit switches allow for safe operation of the system.

CLAWS are easy to install and use a standard SECTOR II controller and a standard SECTOR II gearbox, saving you time and reducing your spares inventory. They boast all-weather construction and have been designed to allow for all moving parts to be removed easily for quick and easy maintenance.

CLAWS also provide onboard support for a traffic light interface, and the Independent Drive **CLAWS** models have variable speed control and multiple Modes of Operation. The **CLAWS** Direct Drive system utilises the SECTOR II traffic barrier's drive mechanism. It is available in both Flush Mount and Surface Mount variants.

The Flush Mount models are ideal for installations that require seamless access control for smooth-flowing traffic, whereas the Surface Mount models are mounted above the general surface of the roadway and create a traffic-calming bump for a safer access control point.


2. Product Specifications

2.1. Technical Specifications


Spike Modules - Available lengths	1 metre and 1.5 metre
Spikes raise / lower time	As per co-installed SECTOR II
Daily operations - Max	50% of co-installed SECTOR II original specification
Daily Operations - Mains present	50% of co-installed SECTOR II original specification
Anti-corrosion - Main chassis	Hot dip galvanised Mild Steel
Spike material	85mm Mild Steel, electroplated and powder-coated
Maximum allowable axel weight	4000kg

2.2. Product Dimensions

2.2.1. Surface Mount





2.2.2. Flush Mount



DIRECT DRIVE SURFACE MOUNT INSTALLATIONS

claws



3. Product Identification




FIGURE 1. PRODUCT IDENTIFICATION

- | | |
|--|--|
| <ul style="list-style-type: none"> 1. Boom pole 2. Spikes module assembly 3. Ramp plates 4. Trench cover plate | <ul style="list-style-type: none"> 5. Spikes 6. Drive linkage assembly 7. SECTOR II |
|--|--|

	Module Frame
	Linkage Frame
	Sandwich Plate
	Top Coupler
	Bottom Coupler
	8x20 Dowel Pin

	Short Drive Arm
	Long Drive Arm
	Linkage Drive Shaft
	Bearing Housing
	Hold Down Bracket
	Con-rod Assembly
	Linkage Cover Plate
	Linkage End Cover
	Module End Cover

4. Tools Required

- 13mm, 17mm, and 19mm Spanners
- Ratchet
- 19mm, and 24mm Sockets
- Allen Key Set
- Mallet
- Tape Measure
- Spirit Level
- Torque Wrench

5. Introduction

This document describes the basic steps to follow when installing the surface-mountable **CLAWS** Spikes driven directly from a SECTOR II Barrier by a “push -pull” linkage system. The installation described in this document is a 2.5 meter installation. For other installations, modules of 1.5 or 1.0 meters can be used to achieve different widths.



The installation of the **CLAWS** Spikes requires a minimum of two persons.

5.1. Installation Configurations

The surface-mountable **CLAWS** Spikes can be installed in four different configurations. The configuration is dependent on two factors:

- Orientation of installation
- Direction of spike impact

5.1.1. Orientation of Installation

The orientation of installation is described as the side at which the drive linkage is installed when approaching the **CLAWS** Spikes. In other words, when driving up to the **CLAWS** Spikes, in the correct direction for traffic flow, and the drive is installed on the right-hand side of the vehicle, it's deemed a right-hand installation. And when driving up to the **CLAWS** Spikes, in the correct direction for traffic flow, and the drive is installed on the left-hand side of the vehicle, it's deemed a left-hand installation.



FIGURE 2. RHS CONFIGURATION



FIGURE 3. LHS CONFIGURATION

5.1.2. Spike Impact Direction

The **CLAWS** Spikes are designed to take a much larger or more frequent impact in one direction. The spikes can be installed to face either towards oncoming traffic (similar) or face towards traffic (opposing) trying to enter from the wrong direction or lane.



FIGURE 4. SPIKE IMPACT DIRECTION - SIMILAR



FIGURE 5. SPIKE IMPACT DIRECTION - OPPOSING

There are four types of typical installations. Refer to Section 5, Figures 2 and 3 to determine if the installation is left- or right-hand orientated.

Secondly; pay attention to the spike impact direction:

- **Similar direction of travel** prevents vehicles from exiting whilst the boom pole is still down (Normal direction of traffic)
- **Opposing direction of travel** prevents vehicles entering against the flow of traffic whilst the boom pole is down




FIGURE 6. RHS SIMILAR DIRECTION OF TRAVEL




FIGURE 7. RHS OPPOSED DIRECTION OF TRAVEL




FIGURE 8. LHS SIMILAR DIRECTION OF TRAVEL





FIGURE 9. LHS OPPOSED DIRECTION OF TRAVEL

6. RHS Surface Mount - Similar Direction of Travel


6.1. Configuring the Drive Linkage Assembly for Right-hand Similar

6.1.1. Stripping the drive linkage assembly




STEP 1

FIGURE 10




STEP 2

FIGURE 11




STEP 3

FIGURE 12




STEP 4

FIGURE 13



STEP 5

FIGURE 14



STEP 6

FIGURE 15

The unit is supplied with two drive arms, RHS and LHS (Section 6, Figure 16).






FIGURE 16




STEP 7

FIGURE 17




STEP 8

FIGURE 18



STEP 9

FIGURE 19



STEP 10

FIGURE 20



The grease nipples on the bearing housings must face up (Section 6, Figures 19 and 20). Take note of the orientation of the Linkage Frame, the Bearing Shaft Assembly, and the Drive Linkage Arm (Section 6, Figure 20).

Once assembled with the long drive arm, the layout should look as shown in Section 6, Figure 21.




FIGURE 21

1. The drive arm must point towards the longer side of the drive linkage assembly (1.5x)
2. The notch must be at the bottom of the shaft (6 o'clock)
3. The bolt head must face the bottom and the nut on top
4. The angle of the bolt and nut must be as shown (11 o'clock)

STEP 11

Replace the bearing housing bolts once everything is in the correct orientation. Hand-tighten for the time being.

SECTION 6

STEP 12

Place the linkage plate back onto the drive linkage assembly without fastening the bolts.

Check that the linkage cover plate is in the correct position and that there is ample clearance for the drive arm (Section 6, Figure 22).

RHS SURFACE MOUNT - SIMILAR DIRECTION OF TRAVEL





FIGURE 22


6.2. Spike Module Assembly

6.2.1. Preparing the Spike Module assembly(ies) for installation




STEP 1

FIGURE 23




STEP 2

FIGURE 24



STEP 3


FIGURE 25



STEP 4


FIGURE 26

6.2.2. Attaching the drive linkage unit to the spike module



STEP 1

FIGURE 27



STEP 2

FIGURE 28



Take note of the orientation of the sandwich plate to the linkage unit before fixing them to the spike module assembly (Section 6, Figure 27).

STEP 3

Using six M12x25 bolts, fix one spike module to another (Section 6, Figure 29).




FIGURE 29



To assist with the alignment and adjustment of the shafts, loosen (but do not remove) the bolts on all of the bearing housings.

6.2.3. Bolting down the assembly to the ground




FIGURE 30



It is crucial that the surface it's mounted on is a reasonably even surface as an uneven surface could result in an uneven binding of the spike shafts. This will result in premature failure.

6.2.4. Assembling the shaft couplings

The coupler is used to connect and align the shafts together.



It is essential that the coupler is assembled correctly; failing to do so will result in slipping of the spikes which is undesirable.




FIGURE 31. SHAFT COUPLER





FIGURE 32




Place the spikes into the down position (and the drive arm pointing upwards) to aid in the fitment of all the shaft couplings.




STEP 1

FIGURE 33




STEP 2

FIGURE 34



STEP 3

FIGURE 35




STEP 4

FIGURE 36


STEP 5

Repeat this coupling process for additional spike modules. Once all shafts have been coupled, check that they move freely.



STEP 6


FIGURE 37



STEP 7

FIGURE 38

6.2.5. Proximity sensor installation



STEP 1

FIGURE 39



The length of the PVC conduit will be relative to the length of the spike modules and drive linkage unit combined. Ensure that a further 110mm is added to this to account for the modules and coupling (Refer to Section 6, Figure 40).





FIGURE 40




Use an appropriate PVC adhesive to bond all conduit lengths, access elbows and couplers to one another.




STEP 2

FIGURE 41




STEP 3

FIGURE 42



STEP 4

FIGURE 43



STEP 5

FIGURE 44



Please ensure that the moving mechanical parts do not rub against the conduit or cables.




FIGURE 45. PROXIMITY SENSOR




FIGURE 46. PROXIMITY SENSOR





FIGURE 47. PROXIMITY SENSOR



STEP 6

FIGURE 48





FIGURE 49




There should be ample cable left over on the drive linkage end, as the wiring will need to be routed up the SECTOR II at a later stage.



STEP 7


FIGURE 50



STEP 8


FIGURE 51

6.3. Re-assembling the ramp plates and linkage cover



STEP 1

FIGURE 52




STEP 2

FIGURE 53



Leave out the four M8 screws and Spring Washers on the far end of the assembly as the module end cover will be assembled later.



STEP 3





FIGURE 54




Take notice of the slot orientation in the trench cover plates before it is placed back into position. The spike must rest on the straight edge of the slot when it is in its upright position.



STEP 4

FIGURE 55




STEP 5

FIGURE 56




It is imperative that the drive linkage cover plate is placed correctly. Make sure that there is clearance for the drive arm to swing through. If this plate is assembled back-to-front the drive arm won't swing through and you will need to turn the plate around (Refer back to Section 6, Figure 22).




STEP 6

FIGURE 57




STEP 7

FIGURE 58




STEP 8

FIGURE 59



STEP 9

FIGURE 60




STEP 10

FIGURE 61


6.4. Integrating the SECTOR II with the CLAWS

6.4.1. Placing the SECTOR II into position



STEP 1

FIGURE 62




STEP 2

FIGURE 63




Lift the spikes by hand to get them just under the level of the trench plate, which pushes the linkage arm back, allowing you to move the unit into its correct position; 110mm from the front edge of the Linkage Cover Plate. (Section 6, Figure 64).



STEP 3

FIGURE 64



STEP 4

FIGURE 65

6.4.2. Fitting and leveling the SECTOR II boom pole


Refer to Section 3.3 of the SECTOR II Installation manual for instructions on fitting and leveling the boom pole.

6.4.3. Inserting the Con-rod



STEP 1

FIGURE 66



STEP 2


FIGURE 67



Apply Lock-tite 243 to all the internal threads and torque both the M16x40 and M16x110 bolts to 40Nm (Steps 3 and 4)




Do not place any body parts near the spikes as serious injury could occur; use the drive arm to move the spikes up and down.



STEP 3

FIGURE 68




STEP 4

FIGURE 69

6.4.4. Adjusting the CLAWS spikes




The CLAWS spikes will raise during this procedure!




STEP 1

FIGURE 70



STEP 2

FIGURE 71



STEP 3

FIGURE 72

With one person holding the barrier pole in the lowered position, adjust the spikes so that the spikes just touch the trench plate (Section 6, Figure 73).





FIGURE 73



STEP 4

FIGURE 74



To ensure correct adjustment, raise the barrier pole and check that the spikes are below the top plate (Section 6, Figures 75 and 76).




FIGURE 75





FIGURE 76


6.5. Completing the Assembly

6.5.1. Fitting the relay enclosure and its bracket




STEP 1

FIGURE 77



STEP 2

FIGURE 78



STEP 3

FIGURE 79

Route the excess wire from the proximity sensor, and wire it to the relay by referring to the wiring diagram (Section 17).




Complete the installation of the SECTOR II as per its full installation manual, and proceed to 'Section 18 - Installation Handover'

7. RHS Surface Mount - Opposing Direction of Travel


7.1. Configuring the Drive Linkage Assembly for Right-hand Similar

7.1.1. Stripping the drive linkage assembly




STEP 1

FIGURE 1




STEP 2

FIGURE 2




STEP 3

FIGURE 3




STEP 4

FIGURE 4



STEP 5

FIGURE 5



STEP 6

FIGURE 6

The unit is supplied with two drive arms, RHS and LHS (see Section 7, Figure 7).






FIGURE 7




STEP 7

FIGURE 8




STEP 8

FIGURE 9



STEP 9

FIGURE 10



STEP 10

FIGURE 11



The grease nipples on the bearing housings must face up (Section 7, Figures 10 and 11). Take note of the orientation of the Linkage frame, the Bearing Shaft Assembly, and the Drive linkage arm (Section 7, Figure 11).

Once assembled with the long drive arm, the format should look as shown in Section 7, Figure 12.




FIGURE 12

1. The drive arm must point towards the longer side of the drive linkage assembly (1.5x)
2. The notch must be at the bottom of the shaft (6 o'clock)
3. The bolt head must face the bottom and the nut on top
4. The angle of the bolt and nut must be as shown (1 o'clock)

STEP 11

Replace the bearing housing bolts once everything is in the correct orientation. Hand-tighten for the time being.

SECTION 7

STEP 12

Place the linkage plate back onto the drive linkage assembly without fastening the bolts.

Check that the linkage cover plate is in the correct position and that there is ample clearance for the drive arm (Section 7, Figure 13).

RHS SURFACE MOUNT - OPPOSING DIRECTION OF TRAVEL





FIGURE 13


7.2. Spike Module Assembly

7.2.1. Preparing the Spike Module assembly(ies) for installation




STEP 1

FIGURE 14




STEP 2

FIGURE 15



STEP 3


FIGURE 16



STEP 4


FIGURE 17

7.2.2. Attaching the drive linkage unit to the spike module



STEP 1

FIGURE 18



STEP 2

FIGURE 19



Take note of the orientation of the sandwich plate to the linkage unit before fixing them to the spike module assembly (Section 7, Figure 18).

STEP 3

Using six M12x25 bolts, fix one spike module to another (Section 7, Figure 20).




FIGURE 20



To assist with the alignment and adjustment of the shafts, loosen (but do not remove) the bolts on all of the bearing housings.

7.2.3. Bolting down the assembly to the ground




FIGURE 21



It is crucial that the surface it's mounted on is a reasonably even surface as an uneven surface could result in an uneven binding of the spike shafts. This will result in premature failure.

7.2.4. Assembling the shaft couplings

The coupler is used to connect and align the shafts together.



It is essential that the coupler is assembled correctly; failing to do so will result in slipping of the spikes which is undesirable.




FIGURE 22. SHAFT COUPLER





FIGURE 23




Place the spikes into the down position (and the drive arm pointing upwards) to aid in the fitment of all the shaft couplings.




STEP 1

FIGURE 24




STEP 2

FIGURE 25



STEP 3

FIGURE 26



STEP 4

FIGURE 27


STEP 5

Repeat this coupling process for additional spike modules. Once all shafts have been coupled, check that they move freely.



STEP 6

FIGURE 28



STEP 7

FIGURE 29

7.2.5. Proximity sensor installation





FIGURE 30

 The length of the PVC conduit will be relative to the length of the spike modules and drive linkage unit combined. Ensure that a further 110mm is added to this to account for the modules and coupling (Refer to Section 7, Figure 31).





FIGURE 31




Use an appropriate PVC adhesive to bond all conduit lengths, access elbows and couplers to one another.




STEP 2

FIGURE 32




STEP 3

FIGURE 33



STEP 4

FIGURE 34



STEP 5

FIGURE 35



Please ensure that the moving mechanical parts do not rub against the conduit or cables.




FIGURE 36. PROXIMITY SENSOR




FIGURE 37. PROXIMITY SENSOR





FIGURE 38. PROXIMITY SENSOR



STEP 6

FIGURE 39





FIGURE 40




There should be ample cable left over on the drive linkage end, as the wiring will need to be routed up the SECTOR II at a later stage.



STEP 7


FIGURE 41



STEP 8


FIGURE 42

7.3. Re-assembling the ramp plates and linkage cover



STEP 1

FIGURE 43




STEP 2

FIGURE 44




Leave out the four M8 screws and Spring Washers on the far end of the assembly as the module end cover will be assembled later.




STEP 3

FIGURE 45




Take notice of the slot orientation in the trench cover plates before it is placed back into position. The spike must rest on the straight edge of the slot when it is in its upright position.



STEP 4

FIGURE 46




STEP 5

FIGURE 47




It is imperative that the drive linkage cover plate is placed correctly. Make sure that there is clearance for the drive arm to swing through. If this plate is assembled back-to-front the drive arm won't swing through and you will need to turn the plate around (Refer back top Section 7, Figure 13).




STEP 6

FIGURE 48




STEP 7

FIGURE 49




STEP 8

FIGURE 50



STEP 9

FIGURE 51




STEP 10

FIGURE 52


7.4. Integrating the SECTOR II with the CLAWS

7.4.1. Placing the SECTOR II into position



STEP 1

FIGURE 53




STEP 2

FIGURE 54




Lift the spikes by hand to get them just under the level of the trench plate, which pushes the linkage arm back, allowing you to move the unit into its correct position; 80mm from the front edge of the Linkage Cover Plate. (Section 7, Figure 55).



STEP 3

FIGURE 55




STEP 4

FIGURE 56

7.4.2. Fitting and leveling the SECTOR II boom pole


Refer to Section 3.3 of the SECTOR II Installation manual for instructions on fitting and leveling to boom pole.

7.4.3. Inserting the Con-rod



STEP 1

FIGURE 57



STEP 2


FIGURE 58



Apply Lock-tite 243 to all the internal threads and torque both the M16x40 and M16x110 bolts to 40Nm (Steps 3 and 4)




Do not place any body parts near the spikes as serious injury could occur; use the drive arm to move the spikes up and down.



STEP 3

FIGURE 59




STEP 4

FIGURE 60

7.4.4. Adjusting the CLAWS spikes




The CLAWS spikes will raise during this procedure!




STEP 1

FIGURE 61



STEP 2

FIGURE 62



STEP 3

FIGURE 63

With one person holding the barrier pole in the lowered position, adjust the spikes so that the spikes just touch the trench plate (Section 7, Figure 64).





FIGURE 64



STEP 4

FIGURE 65



To ensure correct adjustment, raise the barrier pole and check that the spikes are below the top plate (Section 7, Figures 66 and 67).




FIGURE 66





FIGURE 67


7.5. Completing the Assembly

7.5.1. Fitting the relay enclosure and its bracket




STEP 1

FIGURE 68



STEP 2

FIGURE 69



STEP 3

FIGURE 70

Route the excess wire from the proximity sensor, and wire it to the relay by referring to the wiring diagram (Section 16).




Complete the installation of the SECTOR II as per its full installation manual, and proceed to 'Section 17 - Installation Handover'

8. LHS Surface Mount - Similar Direction of Travel


8.1. Configuring the Drive Linkage Assembly for Left-hand Similar

8.1.1. Stripping the drive linkage assembly




STEP 1

FIGURE 1




STEP 2

FIGURE 2




STEP 3

FIGURE 3




STEP 4

FIGURE 4



STEP 5

FIGURE 5



STEP 6

FIGURE 6

The unit is supplied with two drive arms, RHS and LHS (see Section 8, Figure 7).






FIGURE 7




STEP 7

FIGURE 8




STEP 8

FIGURE 9



STEP 9

FIGURE 10



STEP 10

FIGURE 11



The grease nipples on the bearing housings must face up (Section 8, Figures 10 and 11). Take note of the orientation of the Linkage frame, the Bearing Shaft Assembly, and the Drive linkage arm (Section 8, Figure 11).

Once assembled with the short drive arm, the format should look as shown in Section 8, Figure 12.




FIGURE 12

1. The drive arm must point towards the longer side of the drive linkage assembly (1.5x)
2. The notch must be at the bottom of the shaft (6 o'clock)
3. The bolt head must face the bottom and the nut on top
4. The angle of the bolt and nut must be as shown (1 o'clock)

STEP 11

Replace the bearing housing bolts once everything is in the correct orientation. Hand-tighten for the time being.

Step 12

Place the linkage plate back onto the drive linkage assembly without fastening the bolts.

Check that the linkage cover plate is in the correct position and that there is ample clearance for the drive arm (Section 8, Figure 13).





FIGURE 13


8.2. Spike Module Assembly

8.2.1. Preparing the Spike Module assembly(ies) for installation




STEP 1

FIGURE 14




STEP 2

FIGURE 15



STEP 3


FIGURE 16



STEP 4


FIGURE 17

8.2.2. Attaching the drive linkage unit to the spike module



STEP 1

FIGURE 18



STEP 2

FIGURE 19



Take note of the orientation of the sandwich plate to the linkage unit before fixing them to the spike module assembly (Section 8, Figure 18).

Step 3

Using six M12x25 bolts, fix one spike module to another (Section 8, Figure 20).




FIGURE 20



To assist with the alignment and adjustment of the shafts, loosen (but do not remove) the bolts on all of the bearing housings.

8.2.3. Bolting down the assembly to the ground




FIGURE 21



It is crucial that the surface it's mounted on is a reasonably even surface as an uneven surface could result in an uneven binding of the spike shafts. This will result in premature failure.

8.2.4. Assembling the shaft couplings

The coupler is used to connect and align the shafts together.



It is essential that the coupler is assembled correctly; failing to do so will result in slipping of the spikes which is undesirable.




FIGURE 22. SHAFT COUPLER





FIGURE 23




Place the spikes into the down position (and the drive arm pointing upwards) to aid in the fitment of all the shaft couplings.




STEP 1

FIGURE 24




STEP 2

FIGURE 25



STEP 3

FIGURE 26




STEP 4

FIGURE 27


STEP 5

Repeat this coupling process for additional spike modules. Once all shafts have been coupled, check that they move freely.



STEP 6

FIGURE 28



STEP 7

FIGURE 29

8.2.5. Proximity sensor installation




FIGURE 30



The length of the PVC conduit will be relative to the length of the spike modules and drive linkage unit combined. Ensure that a further 110mm is added to this to account for the modules and coupling (Refer to Section 8, Figure 31).





FIGURE 31




Use an appropriate PVC adhesive to bond all conduit lengths, access elbows and couplers to one another.




STEP 2

FIGURE 32




STEP 3

FIGURE 33



STEP 4

FIGURE 34



STEP 5

FIGURE 35



Please ensure that the moving mechanical parts do not rub against the conduit or cables.




FIGURE 36. PROXIMITY SENSOR




FIGURE 37. PROXIMITY SENSOR





FIGURE 38. PROXIMITY SENSOR



STEP 6

FIGURE 39





FIGURE 40




There should be ample cable left over on the drive linkage end, as the wiring will need to be routed up the SECTOR II at a later stage.



STEP 7


FIGURE 41



STEP 8


FIGURE 42

8.3. Re-assembling the ramp plates and linkage cover



STEP 1

FIGURE 43




STEP 2

FIGURE 44



Leave out the four M8 screws and Spring Washers on the far end of the assembly as the module end cover will be assembled later.



STEP 3





FIGURE 45




Take notice of the slot orientation in the trench cover plates before it is placed back into position. The spike must rest on the straight edge of the slot when it is in its upright position.



STEP 4

FIGURE 46




STEP 5

FIGURE 47




It is imperative that the drive linkage cover plate is placed correctly. Make sure that there is clearance for the drive arm to swing through. If this plate is assembled back-to-front the drive arm won't swing through and you will need to turn the plate around (Refer back to Section 8, Figure 13).




STEP 6

FIGURE 48




STEP 7

FIGURE 49




STEP 8

FIGURE 50



STEP 9

FIGURE 51




STEP 10

FIGURE 52


8.4. Integrating the SECTOR II with the CLAWS

8.4.1. Placing the SECTOR II into position



STEP 1

FIGURE 53




STEP 2

FIGURE 54




Lift the spikes by hand to get them just under the level of the trench plate, which pushes the linkage arm back, allowing you to move the unit into its correct position; 110mm from the front edge of the Linkage Cover Plate. (Section 8, Figure 55).



STEP 3

FIGURE 55




STEP 4

FIGURE 56

8.4.2. Fitting and leveling the SECTOR II boom pole


Refer to Section 3.3 of the SECTOR II Installation manual for instructions on fitting and leveling to boom pole.

8.4.3. Inserting the Con-rod



STEP 1

FIGURE 57



STEP 2


FIGURE 58



Apply Lock-tite 243 to all the internal threads and torque both the M16x40 and M16x110 bolts to 40Nm (Steps 3 and 4)




Do not place any body parts near the spikes as serious injury could occur; use the drive arm to move the spikes up and down.



STEP 3

FIGURE 59




STEP 4

FIGURE 60

8.4.4. Adjusting the CLAWS spikes




The CLAWS spikes will raise during this procedure!




STEP 1

FIGURE 61



STEP 2

FIGURE 62



STEP 3

FIGURE 63

With one person holding the barrier pole in the lowered position, adjust the spikes so that the spikes just touch the trench plate (Section 8, Figure 64).





FIGURE 64



STEP 4

FIGURE 65



To ensure correct adjustment, raise the barrier pole and check that the spikes are below the top plate (Section 8, Figures 66 and 67).




FIGURE 66





FIGURE 67


8.5. Completing the Assembly

8.5.1. Fitting the relay enclosure and its bracket




STEP 1

FIGURE 68



STEP 2

FIGURE 69



STEP 3

FIGURE 70

Route the excess wire from the proximity sensor, and wire it to the relay by referring to the wiring diagram (Section 16).




Complete the installation of the SECTOR II as per its full installation manual, and proceed to 'Section 17 - Installation Handover'

9. LHS Surface Mount - Opposing Direction of Travel


9.1. Configuring the Drive Linkage Assembly for Left-hand Similar

9.1.1. Stripping the drive linkage assembly




STEP 1

FIGURE 1




STEP 2

FIGURE 2




STEP 3

FIGURE 3




STEP 4

FIGURE 4



STEP 5

FIGURE 5



STEP 6

FIGURE 6

The unit is supplied with two drive arms, LHS and RHS (see Section 9, Figure 7).






FIGURE 7




STEP 7

FIGURE 8




STEP 8

FIGURE 9



STEP 9

FIGURE 10



STEP 10

FIGURE 11



The grease nipples on the bearing housings must face up (Section 9, Figures 10 and 11). Take note of the orientation of the Linkage frame, the Bearing Shaft Assembly, and the Drive linkage arm (Section 9, Figure 11).

Once assembled with the short drive arm, the format should look as shown in Section 9, Figure 12.




FIGURE 12

1. The drive arm must point towards the longer side of the drive linkage assembly (1.5x)
2. The notch must be at the bottom of the shaft (6 o'clock)
3. The bolt head must face the bottom and the nut on top
4. The angle of the bolt and nut must be as shown (11'clock)

STEP 11

Replace the bearing housing bolts once everything is in the correct orientation. Hand-tighten for the time being.

SECTION 9

STEP 12

Place the linkage plate back onto the drive linkage assembly without fastening the bolts.

Check that the linkage cover plate is in the correct position and that there is ample clearance for the drive arm (Section 9, Figure 13).

LHS SURFACE MOUNT - OPPOSING DIRECTION OF TRAVEL





FIGURE 13


9.2. Spike Module Assembly

9.2.1. Preparing the Spike Module assembly(ies) for installation




STEP 1

FIGURE 14




STEP 2

FIGURE 15



STEP 3


FIGURE 16



STEP 4


FIGURE 17

9.2.2. Attaching the drive linkage unit to the spike module



STEP 1

FIGURE 18



STEP 2

FIGURE 19



Take note of the orientation of the sandwich plate to the linkage unit before fixing them to the spike module assembly (Section 9, Figure 18).

STEP 3

Using six M12x25 bolts, fix one spike module to another (Section 9, Figure 20).




FIGURE 20



To assist with the alignment and adjustment of the shafts, loosen (but do not remove) the bolts on all of the bearing housings.

9.2.3. Bolting down the assembly to the ground




FIGURE 21



It is crucial that the surface it's mounted on is a reasonably even surface as an uneven surface could result in an uneven binding of the spike shafts. This will result in premature failure.

9.2.4. Assembling the shaft couplings

The coupler is used to connect and align the shafts together.



It is essential that the coupler is assembled correctly; failing to do so will result in slipping of the spikes which is undesirable.




FIGURE 22. SHAFT COUPLER





FIGURE 23




Place the spikes into the down position (and the drive arm pointing upwards) to aid in the fitment of all the shaft couplings.




STEP 1

FIGURE 24




STEP 2

FIGURE 25



STEP 3

FIGURE 26



STEP 4

FIGURE 27


STEP 5

Repeat this coupling process for additional spike modules. Once all shafts have been coupled, check that they move freely.



STEP 6

FIGURE 28



STEP 7

FIGURE 29

9.2.5. Proximity sensor installation





FIGURE 30

 The length of the PVC conduit will be relative to the length of the spike modules and drive linkage unit combined. Ensure that a further 110mm is added to this to account for the modules and coupling (Refer to Section 9, Figure 31).





FIGURE 31




Use an appropriate PVC adhesive to bond all conduit lengths, access elbows and couplers to one another.




STEP 2

FIGURE 32




STEP 3

FIGURE 33



STEP 4

FIGURE 34



STEP 5

FIGURE 35



Please ensure that the moving mechanical parts do not rub against the conduit or cables.




FIGURE 36. PROXIMITY SENSOR




FIGURE 37. PROXIMITY SENSOR





FIGURE 38. PROXIMITY SENSOR



STEP 6

FIGURE 39





FIGURE 40




There should be ample cable left over on the drive linkage end, as the wiring will need to be routed up the SECTOR II at a later stage.



STEP 7


FIGURE 41



STEP 8


FIGURE 42

9.3. Re-assembling the ramp plates and linkage cover



STEP 1

FIGURE 43




STEP 2

FIGURE 44




Leave out the four M8 screws and Spring Washers on the far end of the assembly as the module end cover will be assembled later.




STEP 3

FIGURE 45




Take notice of the slot orientation in the trench cover plates before it is placed back into position. The spike must rest on the straight edge of the slot when it is in its upright position.



STEP 4

FIGURE 46




STEP 5

FIGURE 47




It is imperative that the drive linkage cover plate is placed correctly. Make sure that there is clearance for the drive arm to swing through. If this plate is assembled back-to-front the drive arm won't swing through and you will need to turn the plate around (Refer back top Section 9, Figure 13).




STEP 6

FIGURE 48




STEP 7

FIGURE 49




STEP 8

FIGURE 50



STEP 9

FIGURE 51




STEP 10

FIGURE 52


9.4. Integrating the SECTOR II with the CLAWS

9.4.1. Placing the SECTOR II into position



STEP 1

FIGURE 53




STEP 2

FIGURE 54




Lift the spikes by hand to get them just under the level of the trench plate, which pushes the linkage arm back, allowing you to move the unit into its correct position; 80mm from the front edge of the Linkage Cover Plate. (Section 9, Figure 55).



STEP 3

FIGURE 55



STEP 4

FIGURE 56

9.4.2. Fitting and leveling the SECTOR II boom pole


Refer to Section 3.3 of the SECTOR II Installation manual for instructions on fitting and leveling to boom pole.

9.4.3. Inserting the Con-rod



STEP 1

FIGURE 57



STEP 2


FIGURE 58



Apply Lock-tite 243 to all the internal threads and torque both the M16x40 and M16x110 bolts to 40Nm (Steps 3 and 4)




Do not place any body parts near the spikes as serious injury could occur; use the drive arm to move the spikes up and down.



STEP 3

FIGURE 59




STEP 4

FIGURE 60

9.4.4. Adjusting the CLAWS spikes




The CLAWS spikes will raise during this procedure!




STEP 1

FIGURE 61



STEP 2

FIGURE 62



Turning the Con-rod clockwise or anti-closwise will raise or lower the spikes.

Con-rod

STEP 3

FIGURE 63

With one person holding the barrier pole in the lowered position, adjust the spikes so that the spikes just touch the trench plate (Section 9, Figure 71).





FIGURE 64



STEP 4

FIGURE 65



To ensure correct adjustment, raise the barrier pole and check that the spikes are below the top plate (Section 9, Figures 66 and 67).




FIGURE 66





FIGURE 67


9.5. Completing the Assembly

9.5.1. Fitting the relay enclosure and its bracket




STEP 1

FIGURE 68



STEP 2

FIGURE 69



STEP 3

FIGURE 70


Route the excess wire from the proximity sensor, and wire it to the relay by referring to the wiring diagram (Section 16).



Complete the installation of the SECTOR II as per its full installation manual, and proceed to 'Section 17 - Installation Handover'

DIRECT DRIVE FLUSH MOUNT INSTALLATIONS

CLAWS



10. Product Identification










FIGURE 1. PRODUCT IDENTIFICATION

- | | |
|--|--|
| <ul style="list-style-type: none"> 1. Boom pole 2. Spikes module assembly 3. Trench cover plate | <ul style="list-style-type: none"> 4. Spikes 5. Drive linkage assembly 6. SECTOR II |
|--|--|

	Module Frame
	Linkage Frame
	Sandwich Plate
	Top Coupler
	Bottom Coupler
	8x20 Dowel Pin

	Short Drive Arm
	Long Drive Arm
	Linkage Drive Shaft
	Bearing Housing
	Hold Down Bracket
	Con-rod Assembly
	Linkage Cover Plate
	Linkage End Cover
	Module End Cover

11. Tools Required

- 13mm,17mm, 19mm and 24mm Spanners
- Ratchet
- 19mm, and 24mm Sockets
- Allen Key Set
- Mallet
- Tape Measure
- Spirit Level
- Torque Wrench
- Permanent marker
- Spade
- Pick
- Trough
- Fish line
- 50mm hole saw
- Electric Drill

12. Introduction

This document describes the basic steps to follow when installing the flush-mountable **CLAWS** Spikes driven directly from a SECTOR II Barrier by a “push-pull” linkage system. The installation described in this document is a 2.5 meter installation which utilises modules of 1.5 and 1.0 meters.



The installation of the **CLAWS** Spikes requires a minimum of two persons.

12.1. Installation Configurations

The flush-mountable **CLAWS** Spikes can be installed in four different configurations. The configuration is dependent on two factors:

- Orientation of installation
- Direction of spike impact

12.1.1. Orientation of Installation

The orientation of installation is described as the side at which the drive linkage is installed when approaching the **CLAWS** Spikes. In other words, when driving up to the **CLAWS** Spikes, in the correct direction for traffic flow, and the drive is installed on the right-hand side of the vehicle, it's deemed a right-hand installation. And when driving up to the **CLAWS** Spikes, in the correct direction for traffic flow, and the drive is installed on the left-hand side of the vehicle, it's deemed a left-hand installation.



FIGURE 2. RHS CONFIGURATION



FIGURE 3. LHS CONFIGURATION

12.1.2. Spike Impact Direction

The **CLAWS** Spikes are designed to take a much larger impact in one direction. Thus, the **CLAWS** Spikes can be installed to take larger or more frequent impact in one direction. In other words the spikes can be installed to face either towards oncoming traffic (similar) or face towards traffic (opposing) trying to enter from the wrong direction or lane.



FIGURE 4. SPIKE IMPACT DIRECTION - SIMILAR



FIGURE 5. SPIKE IMPACT DIRECTION - OPPOSING

There are four types of typical installations. Refer to Section 12, Figures 2 and 3 to determine if the installation is left- or right-hand orientated.

Secondly; pay attention to the spike impact direction:

- **Similar direction of travel** prevents vehicles from exiting whilst the boom pole is still down (Normal direction of traffic)
- **Opposing direction of travel** prevents vehicles entering against the flow of traffic whilst the boom pole is down




FIGURE 6. RHS SIMILAR DIRECTION OF TRAVEL




FIGURE 7. RHS OPPOSED DIRECTION OF TRAVEL




FIGURE 8. LHS SIMILAR DIRECTION OF TRAVEL





FIGURE 9. LHS OPPOSED DIRECTION OF TRAVEL

13. RHS Flush Mount - Similar Direction of Travel


13.1. Configuring the Drive Linkage Assembly for Right-hand Similar

13.1.1. Stripping the drive linkage assembly




STEP 1

FIGURE 10




STEP 2

FIGURE 11



STEP 3

FIGURE 12



STEP 4

FIGURE 13

The unit is supplied with two drive arms, RHS and LHS (see Section 13, Figure 14).






FIGURE 14




STEP 5

FIGURE 15




STEP 6

FIGURE 16



STEP 7

FIGURE 17



STEP 8

FIGURE 18



The grease nipples on the bearing housings must face up (Section 13, Figures 17 and 18). Take note of the orientation of the Linkage frame, the Bearing Shaft Assembly, and the Drive linkage arm (Section 13, Figure 18).

Once assembled with the long drive arm, the format should look as shown in Section 13, Figure 19.




FIGURE 19

1. The drive arm must point as is shown in Section 13, Figure 19
2. The notch must be at the bottom of the shaft (6 o'clock)
3. The bolt head must face the bottom and the nut on top
4. The angle of the bolt and nut must be as shown (11 o'clock)

STEP 9

Replace the bearing housing bolts once everything is in the correct orientation. Hand-tighten for the time being.

SECTION 13

STEP 10

Place the linkage plate back onto the drive linkage assembly without fastening the bolts.

Check that the linkage cover plate is in the correct position and that there is ample clearance for the drive arm (Section 13, Figure 20).

RHS FLUSH MOUNT - SIMILAR DIRECTION OF TRAVEL





FIGURE 20


13.2. Spike Module Assembly

13.2.1. Preparing the Spike Module assembly(ies) for installation



STEP 1


FIGURE 21



STEP 2


FIGURE 22

13.2.2. Attaching the drive linkage unit to the spike module



STEP 1

FIGURE 23



STEP 2

FIGURE 24



Take note of the orientation of the sandwich plate to the linkage unit before fixing them to the spike module assembly (Section 13, Figure 23).

STEP 3

Using six M12x25 bolts, fix one spike module to another (Section 13, Figure 25).




FIGURE 25



To assist with the alignment and adjustment of the shafts, loosen (but do not remove) the bolts on all of the bearing housings.

13.2.3. Assembling the shaft couplings

The coupler is used to connect and align the shafts together.



It is essential that the coupler is assembled correctly; failing to do so will result in slipping of the spikes which is undesirable.




FIGURE 26. SHAFT COUPLER





FIGURE 27




Place the spikes into the down position (and the drive arm pointing upwards) to aid in the fitment of all the shaft couplings.




STEP 1

FIGURE 28




STEP 2

FIGURE 29



STEP 3

FIGURE 30




STEP 4

FIGURE 31


STEP 5

Repeat this coupling process for additional spike modules. Once all shafts have been coupled, check that they move freely.




STEP 6

FIGURE 32



STEP 7

FIGURE 33

13.2.4. Proximity sensor installation

STEP 1

FIGURE 34



The length of the PVC conduit will be relative to the length of the spike modules combined. Ensure that a further 38mm is added to this to account for the modules and coupling (Refer to Section 13, Figure 35).





FIGURE 35




Use an appropriate PVC adhesive to bond all conduit lengths, access elbows and couplers to one another.




STEP 2

FIGURE 36




STEP 3

FIGURE 37



STEP 4

FIGURE 38



STEP 5

FIGURE 39



Please ensure that the moving mechanical parts do not rub against the conduit or cables.




FIGURE 40. PROXIMITY SENSOR




FIGURE 41. PROXIMITY SENSOR





FIGURE 42. PROXIMITY SENSOR



STEP 6

FIGURE 43






FIGURE 44



There should be ample cable left over on the drive linkage end, as the wiring will need to be routed up the SECTOR II at a later stage.




STEP 7 FIGURE 45




STEP 8 FIGURE 46

13.2.5. Attaching the End Covers to the Assembly

13.2.5.1. Attaching the Module End cover




STEP 1 FIGURE 47




STEP 2 FIGURE 48

13.2.5.2. Attaching the Linkage Unit End cover




STEP 1 FIGURE 49



STEP 2 FIGURE 50

13.3. Preparing the Trench and Drainage System



STEP 1


FIGURE 51



Drainage pipes must be laid at one or both ends of the trench to allow water to flow either into storm water drains or into any other area away from the installation. Section 13, Figure 52 shows two recommended drainage configurations. Once complete, hold the drainage pipes in place by pouring a 100mm concrete foundation and level off.



If the SECTOR II and **CLAWS** are to be separated, a trench for the conduit and cables will need to be dug, and the wiring harnesses will need to be extended in relation to the distance between the gearbox and SECTOR II. This must be done before any concrete is poured (Section 13.5.2.).



STEP 2

FIGURE 52




Ensure that the drain pipes will not interfere with the structure when it is in the trench.

13.3.1. Concreting the Assembly into the Trench.

Place the assembly in the trench and level the assembly using any type of propping or jacking method. Make sure that the top of the assembly is either in line with or a little higher than the ground level and pour concrete (minimum 45MPa after 28 days) into the cavity that remains.



Do not pour any concrete into the gutter of the spikes module or drive link assembly.



STEP 3

FIGURE 53





FIGURE 54. OVERVIEW OF CIVIL LAYOUT

13.4. Re-assembling the trench plate and linkage covers




STEP 1

FIGURE 55




Take notice of the slot orientation in the trench cover plates before it is placed back into position. The spike must rest on the straight edge of the slot when it is in its upright position.



STEP 2

FIGURE 56




STEP 3

FIGURE 57



It is imperative that the drive linkage cover plate is placed correctly. Make sure that there is clearance for the drive arm to swing through. If this plate is assembled back-to-front the drive arm won't swing through and you will need to turn the plate around (Refer back to Section 13, Figure 20).




STEP 3

FIGURE 58


13.5. Integrating the SECTOR II with the CLAWS

13.5.1. Placing the SECTOR II into position



STEP 1

FIGURE 59




STEP 2

FIGURE 60




Lift the spikes by hand to get them just under the level of the trench plate, which pushes the linkage arm back, allowing you to move the unit into its correct position; 110mm from the front edge of the Linkage Cover Plate. (Section 13, Figure 61).



STEP 3

FIGURE 61




STEP 4

FIGURE 62

13.5.2. Fitting and leveling the SECTOR II boom pole


Refer to Section 3.3 of the SECTOR II Installation manual for instructions on fitting and leveling to boom pole.

13.5.3. Inserting the Con-rod



STEP 1

FIGURE 63



STEP 2


FIGURE 64



Apply Lock-tite 243 to all the internal threads and torque the both the M16x40 and M16x110 bolts to 40Nm (Steps 3 and 4)




Do not place any body parts near the spikes as serious injury could occur; use the drive arm to move the spikes up and down.



STEP 3

FIGURE 65




STEP 4

FIGURE 66

13.5.4. Adjusting the CLAWS spikes




The CLAWS spikes will raise during this procedure!



STEP 1


FIGURE 67



STEP 2

FIGURE 68

Turning the Con-rod clockwise or anti-clockwise will raise or lower the spikes.



STEP 3

FIGURE 69

With one person holding the barrier pole in the lowered position, adjust the spikes so that the spikes just touch the trench plate (Section 13, Figure 70).





FIGURE 70



STEP 4

FIGURE 71



To ensure correct adjustment, raise the barrier pole and check that the spikes are below the top plate (Section 13, Figures 72 and 73).




FIGURE 72





FIGURE 73


13.6. Completing the Assembly

13.6.1. Fitting the relay enclosure and its bracket




STEP 1

FIGURE 74



STEP 2

FIGURE 75



STEP 3

FIGURE 76

Route the excess wire from the proximity sensor, and wire it to the relay by referring to the wiring diagram (Section 17).




Complete the installation of the SECTOR II as per its full installation manual, and proceed to 'Section 18 - Installation Handover'

14. RHS Flush Mount - Opposing Direction of Travel


14.1. Configuring the Drive Linkage Assembly for Right-hand Opposing

14.1.1. Stripping the drive linkage assembly




STEP 1

FIGURE 1




STEP 2

FIGURE 2



STEP 3

FIGURE 3



STEP 4

FIGURE 4

The unit is supplied with two drive arms, LHS and RHS (see Section 14, Figure 5).






FIGURE 5




STEP 5

FIGURE 6




STEP 6

FIGURE 7



STEP 7

FIGURE 8



STEP 8

FIGURE 9



The grease nipples on the bearing housings must face up (Section 14, Figures 8 and 9). Take note of the orientation of the Linkage frame, the Bearing Shaft Assembly, and the Drive linkage arm (Section 14, Figure 9).

Once assembled with the long drive arm, the format should look as shown in Section 14, Figure 10.




FIGURE 10

1. The drive arm must point as is shown in Section 14, Figure 10
2. The notch must be at the bottom of the shaft (6 o'clock)
3. The bolt head must face the bottom and the nut on top
4. The angle of the bolt and nut must be as shown (1 o'clock)

STEP 9

Replace the bearing housing bolts once everything is in the correct orientation. Hand-tighten for the time being.

SECTION 14

STEP 10

Place the linkage plate back onto the drive linkage assembly without fastening the bolts.

Check that the linkage cover plate is in the correct position and that there is ample clearance for the drive arm (Section 14, Figure 11).

RHS FLUSH MOUNT - OPPOSING DIRECTION OF TRAVEL





FIGURE 11


14.2. Spike Module Assembly

14.2.1. Preparing the Spike Module assembly(ies) for installation



STEP 1


FIGURE 12



STEP 2


FIGURE 13

14.2.2. Attaching the drive linkage unit to the spike module



STEP 1

FIGURE 14



STEP 2

FIGURE 15



Take note of the orientation of the sandwich plate to the linkage unit before fixing them to the spike module assembly (Section 14, Figure 14).

STEP 3

Using six M12x25 bolts, fix one spike module to another (Section 14, Figure 16).




FIGURE 16



To assist with the alignment and adjustment of the shafts, loosen (but do not remove) the bolts on all of the bearing housings.

14.2.3. Assembling the shaft couplings

The coupler is used to connect and align the shafts together.



It is essential that the coupler is assembled correctly; failing to do so will result in slipping of the spikes which is undesirable.




FIGURE 17. SHAFT COUPLER





FIGURE 18




Place the spikes into the down position (and the drive arm pointing upwards) to aid in the fitment of all the shaft couplings.




STEP 1

FIGURE 19




STEP 2

FIGURE 20



STEP 3

FIGURE 21




STEP 4

FIGURE 22


STEP 5

Repeat this coupling process for additional spike modules. Once all shafts have been coupled, check that they move freely.




STEP 6

FIGURE 23



STEP 7

FIGURE 24

14.2.4. Proximity sensor installation

STEP 1

FIGURE 25



The length of the PVC conduit will be relative to the length of the spike modules combined. Ensure that a further 38mm is added to this to account for the modules and coupling (Refer to Section 14, Figure 26).





FIGURE 26




Use an appropriate PVC adhesive to bond all conduit lengths, access elbows and couplers to one another.




STEP 2

FIGURE 27




STEP 3

FIGURE 28



STEP 4

FIGURE 29



STEP 5

FIGURE 30



Please ensure that the moving mechanical parts do not rub against the conduit or cables.




FIGURE 31. PROXIMITY SENSOR




FIGURE 32. PROXIMITY SENSOR





FIGURE 33. PROXIMITY SENSOR



STEP 6

FIGURE 34






FIGURE 35



There should be ample cable left over on the drive linkage end, as the wiring will need to be routed up the SECTOR II at a later stage.




STEP 7 FIGURE 36




STEP 8 FIGURE 37

14.2.5. Attaching the End Covers to the Assembly

14.2.5.1. Attaching the Module End cover




STEP 1 FIGURE 38




STEP 2 FIGURE 39

14.2.5.2. Attaching the Linkage Unit End cover




STEP 1 FIGURE 40



STEP 2 FIGURE 41

14.3. Preparing the Trench and Drainage System



STEP 1


FIGURE 42



Drainage pipes must be laid at one or both ends of the trench to allow water to flow either into storm water drains or into any other area away from the installation. Section 14, Figure 43 shows two recommended drainage configurations. Once complete, hold the drainage pipes in place by pouring a 100mm concrete foundation and level off.



If the SECTOR II and **CLAWS** are to be separated, a trench for the conduit and cables will need to be dug, and the wiring harnesses will need to be extended in relation to the distance between the gearbox and SECTOR II. This must be done before any concrete is poured (Section 14.5.2.).



STEP 2

FIGURE 43




Ensure that the drain pipes will not interfere with the structure when it is in the trench.

14.3.1. Concreting the Assembly into the Trench.

Place the assembly in the trench and level the assembly using any type of propping or jacking method. Make sure that the top of the assembly is either in line with or a little higher than the ground level and pour concrete (minimum 45MPa after 28 days) into the cavity that remains.

! Do not pour any concrete into the gutter of the spikes module or drive link assembly.



STEP 3

FIGURE 44





FIGURE 45. OVERVIEW OF CIVIL LAYOUT

14.4. Re-assembling the trench plate and linkage covers




STEP 1

FIGURE 46




Take notice of the slot orientation in the trench cover plates before it is placed back into position. The spike must rest on the straight edge of the slot when it is in its upright position.



STEP 2

FIGURE 47




STEP 3

FIGURE 48



It is imperative that the drive linkage cover plate is placed correctly. Make sure that there is clearance for the drive arm to swing through. If this plate is assembled back-to-front the drive arm won't swing through and you will need to turn the plate around (Refer back to Section 14, Figure 11).




STEP 3

FIGURE 49


14.5. Integrating the SECTOR II with the CLAWS

14.5.1. Placing the SECTOR II into position



STEP 1

FIGURE 50




STEP 2

FIGURE 51




Lift the spikes by hand to get them just under the level of the trench plate, which pushes the linkage arm back, allowing you to move the unit into its correct position; 20mm from the front edge of the Linkage Cover Plate. (Section 14, Figure 52).



STEP 3

FIGURE 52




STEP 4

FIGURE 53

14.5.2. Fitting and leveling the SECTOR II boom pole


Refer to Section 3.3 of the SECTOR II Installation manual for instructions on fitting and leveling to boom pole.

14.5.3. Inserting the Con-rod



STEP 1

FIGURE 54



STEP 2


FIGURE 55



Apply Lock-tite 243 to all the internal threads and torque both the M16x40 and M16x110 bolts to 40Nm (Steps 3 and 4)




Do not place any body parts near the spikes as serious injury could occur; use the drive arm to move the spikes up and down.



STEP 3

FIGURE 56




STEP 4

FIGURE 57

14.5.4. Adjusting the CLAWS spikes




The CLAWS spikes will raise during this procedure!



STEP 1


FIGURE 58



STEP 2

FIGURE 59

Turning the Con-rod clockwise or anti-clockwise will raise or lower the spikes.



STEP 3

FIGURE 60

With one person holding the barrier pole in the lowered position, adjust the spikes so that the spikes just touch the trench plate (Section 14, Figure 61).





FIGURE 61



STEP 4

FIGURE 62



To ensure correct adjustment, raise the barrier pole and check that the spikes are below the top plate (Section 14, Figures 63 and 64).




FIGURE 63





FIGURE 64


14.6. Completing the Assembly

14.6.1. Fitting the relay enclosure and its bracket




STEP 1

FIGURE 65



STEP 2

FIGURE 66



STEP 3

FIGURE 67

Route the excess wire from the proximity sensor, and wire it to the relay by referring to the wiring diagram (Section 17).




Complete the installation of the SECTOR II as per its full installation manual, and proceed to 'Section 18 - Installation Handover'


15. LHS Flush Mount - Similar Direction of Travel

15.1. Configuring the Drive Linkage Assembly for Right-hand Similar


15.1.1. Stripping the drive linkage assembly




STEP 1 FIGURE 1



STEP 2 FIGURE 2



STEP 3 FIGURE 3



STEP 4 FIGURE 4

The unit is supplied with two drive arms, LHS and RHS (see Section 15, Figure 5).






FIGURE 5




STEP 5

FIGURE 6




STEP 6

FIGURE 7



STEP 7

FIGURE 8



STEP 8

FIGURE 9



The grease nipples on the bearing housings must face up (Section 15, Figures 8 and 9). Take note of the orientation of the Linkage frame, the Bearing Shaft Assembly, and the Drive linkage arm (Section 15, Figure 9).

Once assembled with the short drive arm, the format should look as shown in Section 15, Figure 10.




FIGURE 10

1. The drive arm must point as is shown in Section 15, Figure 10
2. The notch must be at the bottom of the shaft (6 o'clock)
3. The bolt head must face the bottom and the nut on top
4. The angle of the bolt and nut must be as shown (1 o'clock)

STEP 9

Replace the bearing housing bolts once everything is in the correct orientation. Hand-tighten for the time being.

SECTION 15

LHS FLUSH MOUNT - SIMILAR DIRECTION OF TRAVEL

STEP 10

Place the linkage plate back onto the drive linkage assembly without fastening the bolts.

Check that the linkage cover plate is in the correct position and that there is ample clearance for the drive arm (Section 15, Figure 11).





FIGURE 11


15.2. Spike Module Assembly

15.2.1. Preparing the Spike Module assembly(ies) for installation



STEP 1


FIGURE 12



STEP 2


FIGURE 13

15.2.2. Attaching the drive linkage unit to the spike module



STEP 1

FIGURE 14



STEP 2

FIGURE 15



Take note of the orientation of the sandwich plate to the linkage unit before fixing them to the spike module assembly (Section 15, Figure 14).

STEP 3

Using six M12x25 bolts, fix one spike module to another (Section 15, Figure 16).




FIGURE 16



To assist with the alignment and adjustment of the shafts, loosen (but do not remove) the bolts on all of the bearing housings.

15.2.3. Assembling the shaft couplings

The coupler is used to connect and align the shafts together.



It is essential that the coupler is assembled correctly; failing to do so will result in slipping of the spikes which is undesirable.




FIGURE 17. SHAFT COUPLER





FIGURE 18




Place the spikes into the down position (and the drive arm pointing upwards) to aid in the fitment of all the shaft couplings.




STEP 1

FIGURE 19




STEP 2

FIGURE 20



STEP 3

FIGURE 21




STEP 4

FIGURE 22


STEP 5

Repeat this coupling process for additional spike modules. Once all shafts have been coupled, check that they move freely.




STEP 6

FIGURE 23



STEP 7

FIGURE 24

15.2.4. Proximity sensor installation

STEP 1

FIGURE 25



The length of the PVC conduit will be relative to the length of the spike modules combined. Ensure that a further 38mm is added to this to account for the modules and coupling (Refer to Section 15, Figure 26).





FIGURE 26




Use an appropriate PVC adhesive to bond all conduit lengths, access elbows and couplers to one another.




STEP 2

FIGURE 27




STEP 3

FIGURE 28



STEP 4

FIGURE 29



STEP 5

FIGURE 30



Please ensure that the moving mechanical parts do not rub against the conduit or cables.




FIGURE 31. PROXIMITY SENSOR




FIGURE 32. PROXIMITY SENSOR





FIGURE 33. PROXIMITY SENSOR



STEP 6

FIGURE 34






FIGURE 35



There should be ample cable left over on the drive linkage end, as the wiring will need to be routed up the SECTOR II at a later stage.




STEP 7 FIGURE 36




STEP 8 FIGURE 37

15.2.5. Attaching the End Covers to the Assembly

15.2.5.1. Attaching the Module End cover




STEP 1 FIGURE 38




STEP 2 FIGURE 39

15.2.5.2. Attaching the Linkage Unit End cover




STEP 1 FIGURE 40



STEP 2 FIGURE 41

15.3. Preparing the Trench and Drainage System



STEP 1


FIGURE 42



Drainage pipes must be laid at one or both ends of the trench to allow water to flow either into storm water drains or into any other area away from the installation. Section 15, Figure 43 shows two recommended drainage configurations. Once complete, hold the drainage pipes in place by pouring a 100mm concrete foundation and level off.



If the SECTOR II and **CLAWS** are to be separated, a trench for the conduit and cables will need to be dug, and the wiring harnesses will need to be extended in relation to the distance between the gearbox and SECTOR II. This must be done before any concrete is poured (Section 15.5.2.).



STEP 2

FIGURE 43




Ensure that the drain pipes will not interfere with the structure when it is in the trench.

15.3.1. Concreting the Assembly into the Trench.

Place the assembly in the trench and level the assembly using any type of propping or jacking method. Make sure that the top of the assembly is either in line with or a little higher than the ground level and pour concrete (minimum 45MPa after 28 days) into the cavity that remains.



Do not pour any concrete into the gutter of the spikes module or drive link assembly.



STEP 3

FIGURE 44





FIGURE 45. OVERVIEW OF CIVIL LAYOUT

15.4. Re-assembling the trench plate and linkage covers




STEP 1

FIGURE 46




Take notice of the slot orientation in the trench cover plates before it is placed back into position. The spike must rest on the straight edge of the slot when it is in its upright position.



STEP 2

FIGURE 47




STEP 3

FIGURE 48



It is imperative that the drive linkage cover plate is placed correctly. Make sure that there is clearance for the drive arm to swing through. If this plate is assembled back-to-front the drive arm won't swing through and you will need to turn the plate around (Refer back to Section 15, Figure 11).




STEP 3

FIGURE 49


15.5. Integrating the SECTOR II with the CLAWS

15.5.1. Placing the SECTOR II into position



STEP 1

FIGURE 50




STEP 2

FIGURE 51




Lift the spikes by hand to get them just under the level of the trench plate, which pushes the linkage arm back, allowing you to move the unit into its correct position; 110mm from the front edge of the Linkage Cover Plate. (Section 15, Figure 52).



STEP 3

FIGURE 52




STEP 4

FIGURE 53

15.5.2. Fitting and leveling the SECTOR II boom pole


Refer to Section 3.3 of the SECTOR II Installation manual for instructions on fitting and leveling to boom pole.

15.5.3. Inserting the Con-rod



STEP 1

FIGURE 54



STEP 2


FIGURE 55



Apply Lock-tite 243 to all the internal threads and torque both the M16x40 and M16x110 bolts to 40Nm (Steps 3 and 4)




Do not place any body parts near the spikes as serious injury could occur; use the drive arm to move the spikes up and down.



STEP 3

FIGURE 56



STEP 4

FIGURE 57

15.5.4. Adjusting the CLAWS spikes




The CLAWS spikes will raise during this procedure!




STEP 1

FIGURE 58



STEP 2

FIGURE 59



STEP 3

FIGURE 60

With one person holding the barrier pole in the lowered position, adjust the spikes so that the spikes just touch the trench plate (Section 15, Figure 61).





FIGURE 61



STEP 4

FIGURE 62



To ensure correct adjustment, raise the barrier pole and check that the spikes are below the top plate (Section 15, Figures 62 and 63).




FIGURE 63





FIGURE 64


15.6. Completing the Assembly

15.6.1. Fitting the relay enclosure and its bracket




STEP 1

FIGURE 65



STEP 2

FIGURE 66



STEP 3

FIGURE 66

Route the excess wire from the proximity sensor, and wire it to the relay by referring to the wiring diagram (Section 17).




Complete the installation of the SECTOR II as per its full installation manual, and proceed to 'Section 18 - Installation Handover'

16. LHS Flush Mount - Opposing Direction of Travel


16.1. Configuring the Drive Linkage Assembly for Right-hand Opposing

16.1.1. Stripping the drive linkage assembly




STEP 1

FIGURE 1




STEP 2

FIGURE 2



STEP 3

FIGURE 3



STEP 4

FIGURE 4

The unit is supplied with two drive arms, LHS and RHS (see Section 16, Figure 5).






FIGURE 5




STEP 5

FIGURE 6




STEP 6

FIGURE 7



STEP 7

FIGURE 8



STEP 8

FIGURE 9



The grease nipples on the bearing housings must face up (Section 16, Figures 8 and 9). Take note of the orientation of the Linkage frame, the Bearing Shaft Assembly, and the Drive linkage arm (Section 16, Figure 9).

Once assembled with the short drive arm, the format should look as shown in Section 16, Figure 10.




FIGURE 10

1. The drive arm must point as is shown in Section 16, Figure 10
2. The notch must be at the bottom of the shaft (6 o'clock)
3. The bolt head must face the bottom and the nut on top
4. The angle of the bolt and nut must be as shown (11 o'clock)

STEP 9

Replace the bearing housing bolts once everything is in the correct orientation. Hand-tighten for the time being.

SECTION 16

LHS FLUSH MOUNT - OPPOSING DIRECTION OF TRAVEL

STEP 10

Place the linkage plate back onto the drive linkage assembly without fastening the bolts.

Check that the linkage cover plate is in the correct position and that there is ample clearance for the drive arm (Section 16, Figure 11).





FIGURE 11


16.2. Spike Module Assembly

16.2.1. Preparing the Spike Module assembly(ies) for installation



STEP 1


FIGURE 12



STEP 2


FIGURE 13

16.2.2. Attaching the drive linkage unit to the spike module



STEP 1

FIGURE 14



STEP 2

FIGURE 15



Take note of the orientation of the sandwich plate to the linkage unit before fixing them to the spike module assembly (Section 16, Figure 14).

STEP 3

Using six M12x25 bolts, fix one spike module to another (Section 16, Figure 16).




FIGURE 16



To assist with the alignment and adjustment of the shafts, loosen (but do not remove) the bolts on all of the bearing housings.

16.2.3. Assembling the shaft couplings

The coupler is used to connect and align the shafts together.



It is essential that the coupler is assembled correctly; failing to do so will result in slipping of the spikes which is undesirable.




FIGURE 17. SHAFT COUPLER





FIGURE 18




Place the spikes into the down position (and the drive arm pointing upwards) to aid in the fitment of all the shaft couplings.




STEP 1

FIGURE 19




STEP 2

FIGURE 20



STEP 3

FIGURE 21




STEP 4

FIGURE 22


STEP 5

Repeat this coupling process for additional spike modules. Once all shafts have been coupled, check that they move freely.




STEP 6

FIGURE 23



STEP 7

FIGURE 24

15.2.4. Proximity sensor installation

STEP 1

FIGURE 25



The length of the PVC conduit will be relative to the length of the spike modules combined. Ensure that a further 38mm is added to this to account for the modules and coupling (Refer to Section 16, Figure 26).





FIGURE 26




Use an appropriate PVC adhesive to bond all conduit lengths, access elbows and couplers to one another.




STEP 2

FIGURE 27




STEP 3

FIGURE 28



STEP 4

FIGURE 29



STEP 5

FIGURE 30



Please ensure that the moving mechanical parts do not rub against the conduit or cables.




FIGURE 31. PROXIMITY SENSOR




FIGURE 32. PROXIMITY SENSOR





FIGURE 33. PROXIMITY SENSOR



STEP 6

FIGURE 34





FIGURE 35




There should be ample cable left over on the drive linkage end, as the wiring will need to be routed up the SECTOR II at a later stage.



STEP 7

FIGURE 36




STEP 8

FIGURE 37


16.2.5. Attaching the End Covers to the Assembly

16.2.5.1. Attaching the Module End cover



STEP 1


FIGURE 38



STEP 2


FIGURE 39

16.2.5.2. Attaching the Linkage Unit End cover



STEP 1


FIGURE 40



STEP 2

FIGURE 41

16.3. Preparing the Trench and Drainage System



STEP 1


FIGURE 42



Drainage pipes must be laid at one or both ends of the trench to allow water to flow either into storm water drains or into any other area away from the installation. Section 16, Figure 43 shows two recommended drainage configurations. Once complete, hold the drainage pipes in place by pouring a 100mm concrete foundation and level off.



If the SECTOR II and **CLAWS** are to be separated, a trench for the conduit and cables will need to be dug, and the wiring harnesses will need to be extended in relation to the distance between the gearbox and SECTOR II. This must be done before any concrete is poured (Section 16.5.2.).



STEP 2

FIGURE 43




Ensure that the drain pipes will not interfere with the structure when it is in the trench.

16.3.1. Concreting the Assembly into the Trench.

Place the assembly in the trench and level the assembly using any type of propping or jacking method. Make sure that the top of the assembly is either in line with or a little higher than the ground level and pour concrete (minimum 45MPa after 28 days) into the cavity that remains.



Do not pour any concrete into the gutter of the spikes module or drive link assembly.



STEP 3

FIGURE 44





FIGURE 45. OVERVIEW OF CIVIL LAYOUT

16.4. Re-assembling the trench plate and linkage covers




STEP 1

FIGURE 46




Take notice of the slot orientation in the trench cover plates before it is placed back into position. The spike must rest on the straight edge of the slot when it is in its upright position.



STEP 2

FIGURE 47




STEP 3

FIGURE 48



It is imperative that the drive linkage cover plate is placed correctly. Make sure that there is clearance for the drive arm to swing through. If this plate is assembled back-to-front the drive arm won't swing through and you will need to turn the plate around (Refer back to Section 16, Figure 11).




STEP 3

FIGURE 49


16.5. Integrating the SECTOR II with the CLAWS

16.5.1. Placing the SECTOR II into position



STEP 1

FIGURE 50




STEP 2

FIGURE 51




Lift the spikes by hand to get them just under the level of the trench plate, which pushes the linkage arm back, allowing you to move the unit into its correct position; 20mm from the front edge of the Linkage Cover Plate. (Section 16, Figure 52).



STEP 3

FIGURE 52




STEP 4

FIGURE 53

16.5.2. Fitting and leveling the SECTOR II boom pole


Refer to Section 3.3 of the SECTOR II Installation manual for instructions on fitting and leveling to boom pole.

16.5.3. Inserting the Con-rod



STEP 1

FIGURE 54



STEP 2


FIGURE 55



Apply Lock-tite 243 to all the internal threads and torque both the M16x40 and M16x110 bolts to 40Nm (Steps 3 and 4)




Do not place any body parts near the spikes as serious injury could occur; use the drive arm to move the spikes up and down.



STEP 3

FIGURE 56




STEP 4

FIGURE 57

16.5.4. Adjusting the CLAWS spikes




The CLAWS spikes will raise during this procedure!




STEP 1

FIGURE 58



STEP 2

FIGURE 59



STEP 3

FIGURE 60

With one person holding the barrier pole in the lowered position, adjust the spikes so that the spikes just touch the top plate (Section 16, Figure 61).





FIGURE 61



STEP 4

FIGURE 62



To ensure correct adjustment, raise the barrier pole and check that the spikes are below the top plate (Section 16, Figures 63 and 64).




FIGURE 63





FIGURE 64


16.6. Completing the Assembly

16.6.1. Fitting the relay enclosure and its bracket




STEP 1

FIGURE 65



STEP 2

FIGURE 66



STEP 3

FIGURE 67

Route the excess wire from the proximity sensor, and wire it to the relay by referring to the wiring diagram (Section 17).



Complete the installation of the SECTOR II as per its full installation manual, and proceed to 'Section 18 - Installation Handover'

17. Wiring Diagram




FIGURE 68

18. Installation Handover

Once the installation has been successfully completed and tested, it is important to explain the operation and safety requirements of the system to the end-user.

NEVER ASSUME THE USER KNOWS HOW TO SAFELY OPERATE AUTOMATED ROADWAY SPIKES!

Even if the user has used such a system before, it does not mean he knows how to SAFELY operate it. Make sure that the user fully understands the following safety requirements before finally handing over the site.

The following needs to be understood by the user:

- How co-installed safety loops and all other safety features work
(Show them how by demonstration)
- All the features and benefits of the spikes
- **All the safety considerations associated with operating automated roadway spikes.**

The user should be able to pass this knowledge on to all other users of the automated system and must be made aware of this responsibility

- Do not activate the CLAWS unless you can see it and can determine that its area of travel is clear of people, pets, or other obstructions
- **NO ONE MAY PASS OVER RAISING SPIKES.** Always keep people and objects away from the spikes
- **NEVER LET CHILDREN OPERATE OR PLAY WITH THE SPIKE CONTROLS,** and do not allow children or pets near the spike area
- Be careful with moving parts and avoid close proximity to areas where fingers or hands could be pinched
- Secure all easily-accessed spike controls in order to prevent its unauthorised use
- Keep the automated spikes system properly maintained, and ensure that all working areas are free of objects that could affect its operation and safety
- On a monthly basis, check the obstruction detection system and safety devices for correct operation
- All repair and service work to this product must be done by a suitably qualified person
- This product was designed and built strictly for the use indicated in this documentation. Any other use, not expressly indicated here, could compromise the good condition/operation of the product and/or be a source of danger!



Neither Centurion Systems (Pty) Ltd, nor its subsidiaries, accepts any liability caused by improper use of the product, or for use other than that for which the automated system was intended.

Ensure that the customer is in possession of the user guide and that you have completed the installation details in the back of the manual.



Connect with us on:

 facebook.com/centurionsystems

 YouTube.com/centurionsystems

 [@askcenturion](https://twitter.com/askcenturion)

Subscribe to the newsletter: www.centsys.com/subscribe

**Call Centurion Systems (Pty) Ltd · South Africa
Head Office: +27 11 699 2400**

**Call Technical Support: +27 11 699 2481
Monday to Friday: from 07h00 to 18h00 (GMT+2)
Saturday: from 08h00 to 16h30 (GMT+2)**

E&OE Centurion Systems (Pty) Ltd reserves the right to change any product without prior notice

All product and brand names in this document that are accompanied by the ® symbol are registered trademarks in South Africa and/or other countries, in favour of Centurion Systems (Pty) Ltd, South Africa.

The CENTURION and CENTSYS logos, all product and brand names in this document that are accompanied by the TM symbol are trademarks of Centurion Systems (Pty) Ltd, in South Africa and other territories; all rights are reserved.

We invite you to contact us for further details.



**Doc number: 1307.D.01.0004_2
SAP code: DOC1307D04**

www.centsys.com