



CENTURION

GSM-based Devices Comparison Chart

| Technical Data | G-SWITCH-22 | MyGSM 2120 | MyGSM 8180 |
|--------------------------------|-------------------------|---------------------|---------------------------------|
| Input voltage range | 11V - 30V DC | 9V - 12V DC | 12V - 24V DC |
| Number of inputs | 2 | 2 | 8 |
| Number of outputs | 2 | 2 | 8 |
| Microphone and speaker | – | Optional microphone | Optional microphone and speaker |
| Expandable inputs | – | – | Expansion port available |
| Expandable outputs | – | – | Expansion port available |
| Web interface | Yes | Yes | Yes |
| Reacts to: SMS and Missed Call | Yes | Yes | Yes |
| Reacts to: Please Call Me | – | Yes | Yes |
| Programming | Web and SMS | Web, SMS and USB | Web, SMS and USB |
| Maximum number of users | 1200 | 5000 | 5000 |
| Full reporting | Web-based | Web-based | Web-based |
| Limited uses counter | Based on number of uses | Time-based | Time-based |
| Automatic activations | – | Yes | Yes |
| Standby current | 100mA | 85mA | 50mA |
| Number of SIM card slots | 1 | 1 | 2 |
| Airtime query | Yes, via SMS | Yes, via SMS | Yes, via SMS |